ROBBINS[®] **Delicate Expressions**[®] Porcelain Stone[®]

Available Colors



RR84401 ▶ Morning Light



RR84403 ▶ Welcoming Dawn



RR84405 ▶ Tea Time



RR84407 ▶ Evening Stroll



RR84409 ▶ Nightfall

Available Mosaics



2 x 4 Stacked Mosaics (available in all colors)



1 x 6 Stacked Mosaics (available in all colors)

Features and Benefits

- Transform your living spaces with the elegant, organic beauty of Delicate Expressions" porcelain tile by Robbins.
- Available in five essential colors and working alongside, or in lieu of, natural wood, these eco-friendly porcelain tiles are meticulously crafted for perfect plank alignment.
- Delicate Expressions generous 8"x48" planks offer enduring strength and durability for indoor and outdoor spaces.
- Expand your design options with cove base and bullnose trim along with 2x4 and 1x6 stacked mosaic that are perfect for shower pans and pool lines
- Made in the USA and Green Squaresm Certified

ROBBINS Delicate Expressions Porcelain Stone

Field Tile - Rectified			Available in all colors	
Nominal (in)	Actual (mm)	Thickness (mm)	Grout Joint (mm)	Finish
8 x 48 Note: Field tile is rectified wit	197 x 1197 h a 3mm grout joint	10.5	3	UPS/EXT
Mosaics			Available in all colors	
Nominal (in)	Sheet Size (mm)	Thickness (mm)	Grout Joint (mm)	Finish
2 x 4 Stacked*	297 x 297	10.5	2.5	UPS
1 x 6 Stacked	297 x 290	10.5	3	UPS
 Mounted on 12 x 12 sheet (cov Mounted on 12 x 11 sheet (cov 				
Coordinating Trim			Available in all colors †	
Nominal (in)	Actual (mm)	Thickness (mm)	Grout Joint (mm)	Finish
4 x 24 Single Bullnose	97 x 597	10.5	3	UPS
6 x 12 Cove Base	150 x 297	10.5	3	UPS
η	4 x 24 Single	6 x 12 C	ove Base	
	4 x 24 Single Bullnose 6 x 12 Cove Base		010 2000	
Product Performance Water Absorption		<0.50%	ASTM C373	
Breaking Strength		>450 lbf	ASTM C648	
Bond Strength		>200 psi	ASTM C482	
Facial Dimension		±0.10%	ASTM C1026	
		0.035 in	ASTM C499	
Range of Thickness (In)				
Range of Thickness (In) Warpage - diagonal		±0.20%	ASTM C485	
Warpage - diagonal		±0.20% ±0.30%	ASTM C485 ASTM C502	
······································				
Warpage - diagonal Wedging		±0.30%	ASTM C502	5
Warpage - diagonal Wedging Frost Resistance		±0.30% Resistant	ASTM C502 ASTM C1026	5
Warpage - diagonal Wedging Frost Resistance Chemical Resistance Scratch Hardness	nt of Friction Range	±0.30% Resistant Unaffected	ASTM C502 ASTM C1020 ASTM C650	5
Warpage - diagonal Wedging Frost Resistance Chemical Resistance	nt of Friction Range	±0.30% Resistant Unaffected	ASTM C502 ASTM C1020 ASTM C650 Mohs Scale	5
Warpage - diagonal Wedging Frost Resistance Chemical Resistance Scratch Hardness Wet Dynamic Coefficien	nt of Friction Range	±0.30% Resistant Unaffected 7	ASTM C502 ASTM C1020 ASTM C650 Mohs Scale	5
Warpage - diagonal Wedging Frost Resistance Chemical Resistance Scratch Hardness Wet Dynamic Coefficien UPS EXT	nt of Friction Range	±0.30% Resistant Unaffected 7 0.50 - 0	ASTM C502 ASTM C1020 ASTM C650 Mohs Scale	5 II A326.3
Warpage - diagonal Wedging Frost Resistance Chemical Resistance Scratch Hardness Wet Dynamic Coefficien UPS EXT Shade & Texture Index		±0.30% Resistant Unaffected 7 0.50 - 0 0.60 - 0	ASTM C502 ASTM C1020 ASTM C650 Mohs Scale	5 II A326.3
Warpage - diagonal Wedging Frost Resistance Chemical Resistance Scratch Hardness Wet Dynamic Coefficien UPS EXT Shade & Texture Index Delicate Expressions has		±0.30% Resistant Unaffected 7 0.50 - 0 0.60 - 0	ASTM C502 ASTM C1020 ASTM C650 Mohs Scale .60 ANS .70 ANS	5 I A326.3 I A326.3
Warpage - diagonal Wedging Frost Resistance Chemical Resistance Scratch Hardness Wet Dynamic Coefficien UPS EXT Shade & Texture Index		±0.30% Resistant Unaffected 7 0.50 - 0 0.60 - 0	ASTM C502 ASTM C1026 ASTM C650 Mohs Scale 60 ANS 70 ANS V1 Uniform appea	5 II A326.3 II A326.3 II A326.3
Warpage - diagonal Wedging Frost Resistance Chemical Resistance Scratch Hardness Wet Dynamic Coefficien UPS EXT Shade & Texture Index Delicate Expressions has		±0.30% Resistant Unaffected 7 0.50 - 0 0.60 - 0	ASTM C502 ASTM C1020 ASTM C650 Mohs Scale .60 ANS .70 ANS V1 Uniform appea V2 Slight Variation	5 II A326.3 II A326.3 II A326.3 mrance
Warpage - diagonal Wedging Frost Resistance Chemical Resistance Scratch Hardness Wet Dynamic Coefficien UPS EXT Shade & Texture Index Delicate Expressions has		±0.30% Resistant Unaffected 7 0.50 - 0 0.60 - 0	ASTM C502 ASTM C1026 ASTM C650 Mohs Scale 60 ANS 70 ANS V1 Uniform appea	5 II A326.3 II A326.3 II A326.3 mrance



Sizes

8 x 48

2 x 4 Stacked Mosaid Mounted on a 297 x 297 sheet



1 x 6 Stacked Mosaic Mounted on a 297 x 290 sheet

Get Planked!

Our Porcelain Stone^{*} products are available in popular plank shapes with no minimum order and quick fulfillment.

See website for more details and sizes.





ROBBINS[®] **Delicate Expressions**[®] Porcelain Stone[®]

Application Areas

Recommended Use

T I							
Finish	Interior Floors (dry)	Interior Walls (wet/dry)	Exterior Walls	Interior Floors (Standing water/ shower floors)	Exterior/Paving	Pool/Fountain Full Lining**	Water Line Pool/ Fountains
UPS	\checkmark	\checkmark	\checkmark			\checkmark	\checkmark
EXT	\checkmark	\checkmark	\checkmark	\checkmark	\checkmark	\checkmark	\checkmark

** Excludes mesh mounted mosaics. Robbins recommends face mounted or edge mounted mosaics for fully submerged applications. Contact your Robbins sales representative for more information.

NOTE: Trim applications will differ from field tile applications for the same series.

For more information on ANSI- A362.3 visit our website at https://www.robbins.com

Delicate Expressions[¬] UPS is recommended for interior floors dry, interior walls, countertops, exterior walls, pool waterlines and full linings[†] in both residential and commercial applications. Delicate Expressions UPS is not recommended for exterior horizontal surfaces or exterior paving. Delicate Expressions EXT is recommended for interior or exterior floors and walls in both residential and commercial applications.

† Excludes mesh mounted mosaics.

Care and Maintenance

Regular cleaning is the best way to keep Delicate Expressions tile looking good for years to come. Use clean, hot water(combined with a household cleaner for more aggressive cleaning). Rinse thoroughly and dry with a soft cloth. No waxes are needed. More information regarding the care and maintenance of Robbins products is available at Robbins. com.

Wet area use for Mosaics

Robbins[°] produces the Delicate Expressions 2x4 stacked mosaic and 1x6 stacked Mosaics with the Cross-Sheen (UPS) finish. The ANSI A326.3 wet Dynamic COF of Delicate Expressions is ≥0.50. Their small sizes ensure frequent grout joints which provides traction and drainage. Robbins cannot control situations involving incorrect installation, improper slope to the drain for elimination of standing water and poor surface cleaning.

This information is provided so that customers may make a realistic and informed decision when comparing Delicate Expressions to other tile products in wet area environment, such as residential/commercial bathrooms, showers, and interior pool decks. Information listed here is subject to change.

Please refer to Robbins.com for the latest, most accurate information.

Our Warranty

Robbins guarantees that its products will meet or exceed the performance specifications outlined in ANSI A137.1 and in the performance data section of the Robbins general product catalog. For complete details check our website at Robbins.com.

Information listed here is subject to change. Please refer to Robbins.com for the latest, most accurate information.

Crossville[®] Sample Express

Complimentary Samples are available at **Robbins.com**

Loose Tile Samples

Sizes may vary depending on product series Max. of 4 large field tile per order

Standard Shipping FedEx Ground













