

ROBBINS[®] Lisbon Impressions[™] Porcelain Stone[®]



ROBBINS®

Lisbon Impressions™ Porcelain Stone®

Take a trip to Portugal with Robbins.

Inspired by Portuguese Atlantic Dark limestone, Lisbon Impressions porcelain stone collection is graced with natural beauty found only in the Mediterranean. The look of the limestone captured in this line is different from others of its kind, featuring a subtle, organic surface that delivers a sophisticated, tactile elegance. The six hues in Lisbon Impression color palette are a mix of warm and cool neutrals designed to coordinate with some of our best-selling collections, providing an even broader spectrum of Robbins tiles to mix and match for your projects.

Lisbon Impression is not only unique in its look, but also its feel. This line comes in interior and exterior finishes, offering ideal solutions for installations that flow from indoors to out. Lisbon Impression interior unpolished field tiles range from extra large 24"x48" to 6"x24", and the textured exterior sizes, designed to an average minimum 0.60 DCOF and R11 classified, come in 12"x24" and 24"x24". The line's distinct triangular mosaic opens many design possibilities for floors and walls; it works with both linear and centered drains on wet area floors and creates a stunning vertical focal point when taken to the wall. Need something more subtle? We also offer a traditional 2"x2" mosaic. Complete your installations with bullnose or cove base made from the same material as the field tile to ensure coordination.



PT22454 ▶ Castelo Fog 24 x 24 EXT



Wall: PT24445 ▶ Clásica White 12 x 24 UPS

Color Palette

Available Colors

COOL

LIGHT



PT22443 ▶ Clássica White

WARM




PT22448 ▶ Blushing Rosé

MID



PT22453 ▶ Castelo Fog

Available Mosaics



PTG01.10202UMOS ▶
Classica White (Cool Light)
2 x 2 Mosaic



PTG03.10202UMOS ▶
Castelo Fog (Cool Mid)
2 x 2 Mosaic



PTG02.10202UMOS ▶
Blushing Rosé (Warm Light)
2 x 2 Mosaic



PTG01.1CRSUMOS ▶
Classica White (Cool Light)
Geometric Mosaic†



PTG03.1CRSUMOS ▶
Castelo Fog (Cool Mid)
Geometric Mosaic†



PTG02.1CRSUMOS ▶
Blushing Rosé (Warm Light)
Geometric Mosaic†


† Due to this mosaic's design, caution should be used when installing on surfaces that might contact bare skin or other delicate materials. To prevent possible injury or damage from sharp corners that might be exposed above the grout line, install per ANSI 108 guidelines in order to minimize or prevent lippage.

Specifications

Sizes



24 x 48



24 x 24

12 x 24



6 x 24



Geometric Mosaic†
(Mounted on a 217 x 372 mm sheet)

2 x 2 Mosaic
(Mounted on a 298 x 298 mm sheet)

† Due to this mosaic's design, caution should be used when installing on surfaces that might contact bare skin or other delicate materials. To prevent possible injury or damage from sharp corners that might be exposed above the grout line, install per ANSI 108 guidelines in order to minimize or prevent lippage.

Get Planked!

Our Porcelain Stone® products are available in popular plank shapes with no minimum order and quick fulfillment.

See website for more details and sizes.



Sizes & Finishes

Field Tile - Rectified

Available in all colors

Nominal (in)	Actual (mm)	Thickness (mm)	Grout Joint (mm)	Finish
6 x 24	147 x 597	9.5	3	UPS
12 x 24	297 x 597	9.5	3	UPS/EXT
24 x 24	597 x 597	9.5	3	UPS/EXT
24 x 48	597 x 1197	10.5	3	UPS

Robbins recommends a grout joint of 3mm.
Actual measurements stated in inches indicate tile is calibrated (non-rectified).
Actual measurements stated in mm indicate tile is rectified.

Mosaics

Available in all colors

Nominal (in)	Actual Size (mm)	Thickness (mm)	Grout Joint (mm)	Finish
2 x 2 Mosaic*	298 x 298	9.5	3	UPS
Geometric Mosaic†	217 x 372	9.5	2	UPS

* Mounted on 12 x 12 sheet with 3mm grout joints

† Due to this mosaic's design, caution should be used when installing on surfaces that might contact bare skin or other delicate materials. To prevent possible injury or damage from sharp corners that might be exposed above the grout line, install per ANSI 108 guidelines in order to minimize or prevent lippage.

Coordinating Trim

Available in all colors

Nominal (in)	Actual (mm)	Thickness (mm)	Grout Joint (mm)	Finish
6 x 12 Cove Base	150 x 297	9.5	3	UPS
4 x 24 Single Bullnose	96 x 597	9.5	3	UPS



6 x 12
Cove Base



4 x 24 Bullnose

Product Performance

Breaking Strength	>450 lbf	ASTM C648
Bond Strength	>200 psi	ASTM C482
Chemical Resistance	Unaffected	ASTM C650
Frost Resistance	Resistant	ASTM C1026
Water Absorption	<0.50%	ASTM C373
Scratch Hardness	7	Mohs Scale

Wet Dynamic Coefficient of Friction Range

UPS	0.50 - 0.60	ANSI A326.3
EXT (Textured)	0.60 - 0.70	ANSI A326.3

Shade & Texture Index

Lisbon Impressions has a shade variation of V2.

V1	V2	V3	V4	V1 Uniform appearance
				V2 Slight Variation
				V3 Moderate Variation
				V4 Substantial Variation

This porcelain tile product is produced with a V2 variation. Expect that the amount of color and texture on each piece may vary slightly. Inspect the product upon delivery and for best results, blend tile from several cartons during installation.

Recommended Use

Lisbon Impressions UPS is recommended for interior floors, interior walls, countertops, exterior walls, pool waterlines and full linings[†] in both residential and commercial applications. Lisbon Impressions UPS is not recommended for exterior horizontal surfaces or exterior paving. Lisbon Impressions EXT is recommended for exterior floors and walls in both residential and commercial applications. See Robbins.com for detailed installation instructions.

[†] Excludes mesh mounted mosaics.

Care and Maintenance

Regular cleaning is the best way to keep Lisbon Impressions tile looking good for years to come. Use clean, hot water (combined with a household cleaner for more aggressive cleaning). Rinse thoroughly and dry with a soft cloth to prevent water spots. No waxes or sealers are needed. More information regarding the care and maintenance of Robbins products is available at Robbins.com

Wet area use for mosaics

Robbins' produces the Lisbon Impressions 2 x 2 and Robbins mosaics with the Unpolished (UPS) finish. The ANSI A326.3 wet Dynamic COF of Lisbon Impressions is ≥ 0.42 . Their small sizes ensure frequent grout joints which provides traction and drainage. Robbins cannot control situations involving incorrect installation, improper slope to the drain for elimination of standing water and poor surface cleaning. This information is provided so that customers may make a realistic and informed decision when comparing Lisbon Impressions to other tile products in wet area environments, such as residential/commercial bathrooms, showers, and interior pool decks.

information listed here is subject to change. Please refer to Robbins.com for the latest, most accurate information.

Care and Maintenance

Regular cleaning is the best way to keep Lisbon Impressions tile looking good for years to come. Use clean, hot water (combined with a household cleaner for more aggressive cleaning). Rinse thoroughly and dry with a soft cloth to prevent water spots. No waxes or sealers are needed. More information regarding the care and maintenance of Robbins products is available at Robbins.com.

Our Warranty

Robbins Inc guarantees that its products will meet or exceed the performance specifications outlined in ANSI A137.1-2021 and in the performance data section of the Robbins, general product catalog. For complete details check our website at Robbins.com.

Trade Organizations



Environmentally Aware



Lisbon Impressions™

AHF Products

3840 Hempland Rd.
Mountville, PA
17554

Phone 866 243-2726
Web Robbins.com



ROBBINS®