

# ROBBINS® Lisbon Impressions™ Porcelain Stone®

## Available Colors

### COOL

LIGHT



PT22443 ▶ Clássica White

### WARM



PT22448 ▶ Grand Rosé

MID



PT22453 ▶ Castelo Fog


## Available Colors

- Inspired by Portuguese Atlantic Dark limestone
- The three hues in Lisbon Impressions color palette are a mix of warm and cool neutrals designed to coordinate with some of our best-selling collections
- This line comes in interior and exterior finishes, for installations that flow from indoors to out.
- Interior unpolished field tiles range 24"x48" to 6"x24"
- The textured exterior sizes, designed to an average minimum 0.60 DCOF and R11 classified, come in 12"x24" and 24"x24".
- The line's distinct triangular mosaic opens many design possibilities for floors and walls along with a 2"x2" mosaic.
- Complete your installations with 4 x 24 bullnose or 6 x 12 cove base

# ROBBINS®

# ROBBINS® Lisbon Impressions™ Porcelain Stone®

## Lisbon Impressions 2 x 2 and Robbins Mosaics



**PTG01.10202UMOS ▶**  
Classica White (Cool Light)  
2 x 2 Mosaic



**PTG03.10202UMOS ▶**  
Castelo Fog (Cool Mid)  
2 x 2 Mosaic



**PTG02.10202UMOS ▶**  
Blushing Rosé (Warm Light)  
2 x 2 Mosaic



**PTG01.1CRSUMOS ▶**  
Classica White (Cool Light)  
Geometric Mosaic†



**PTG03.1CRSUMOS ▶**  
Castelo Fog (Cool Mid)  
Geometric Mosaic†




**PTG02.1CRSUMOS ▶**  
Blushing Rosé (Warm Light)  
Geometric Mosaic†

† Due to this mosaic's design, caution should be used when installing on surfaces that might contact bare skin or other delicate materials. To prevent possible injury or damage from sharp corners that might be exposed above the grout line, install per ANSI 108 guidelines in order to minimize or prevent lippage.

# ROBBINS® Lisbon Impressions™ Porcelain Stone®

## Sizes



Geometric Mosaic†

(Mounted on a 217 x 372 mm sheet)

2 x 2 Mosaic

(Mounted on a 298 x 298 mm sheet)

† Due to this mosaic's design, caution should be used when installing on surfaces that might contact bare skin or other delicate materials. To prevent possible injury or damage from sharp corners that might be exposed above the grout line, install per ANSI 108 guidelines in order to minimize or prevent lippage.

## Get Planked!

Our Porcelain Stone® products are available in popular plank shapes with no minimum order and quick fulfillment.

See website for more details and sizes.



## Application Areas

Finish	Interior Floors (dry)	Interior Walls (wet/dry)	Exterior Walls	Interior Floors (Standing water/shower floors)	Exterior/Paving	Pool/Fountain Full Lining**	Water Line Pool/Fountains
UPS	✓	✓	✓	Mosaics Only*		✓	✓
EXT	✓	✓	✓		✓	✓	✓

\*\* Excludes mesh mounted mosaics. Robbins recommends face mounted or edge mounted mosaics for fully submerged applications. Contact your Robbins sales representative for more information.

NOTE: Trim applications will differ from field tile applications for the same series.

For more information on ANSI- A362.3 visit our website at <https://www.robbins.com>

AHF Products • 3840 Hempland Rd, Mountville, PA 17554 • Phone: 866 243-2726 • Robbins.com

## Sizes & Finishes

### Field Tile - Rectified

Available in all colors

Nominal (in)	Actual (mm)	Thickness (mm)	Grout Joint (mm)	Finish
6 x 24	147 x 597	9.5	3	UPS
12 x 24	297 x 597	9.5	3	UPS/EXT
24 x 24	597 x 597	9.5	3	UPS/EXT
24 x 48	597 x 1197	10.5	3	UPS

Robbins recommends a grout joint of 3mm.

Actual measurements stated in inches indicate tile is calibrated (non-rectified).

Actual measurements stated in mm indicate tile is rectified.

### Mosaics

Available in all colors

Nominal (in)	Actual Size (mm)	Thickness (mm)	Grout Joint (mm)	Finish
2 x 2 Mosaic*	298 x 298	9.5	3	UPS
Geometric Mosaic***	217 x 372	9.5	2	UPS

\*\* Mounted on 298mm x 298mm sheet with 3mm grout joints (Coverage area 0.9752 sf)

\*\*\* Mounted on 217mm x 372mm sheet with 2mm grout joints (Coverage area 0.5780 sf)

† Due to this mosaic's design, caution should be used when installing on surfaces that might contact bare skin or other delicate materials. To prevent possible injury or damage from sharp corners that might be exposed above the grout line, install per ANSI 108 guidelines in order to minimize or prevent lippage.

### Coordinating Trim

Available in all colors

Nominal (in)	Actual (mm)	Thickness (mm)	Grout Joint (mm)	Finish
6 x 12 Cove Base	150 x 297	9.5	3	UPS
4 x 24 Single Bullnose	96 x 597	9.5	3	UPS



6 x 12 Cove Base



4 x 24 Bullnose

## Product Performance

Breaking Strength	>450 lbf	ASTM C648
Bond Strength	>200 psi	ASTM C482
Chemical Resistance	Unaffected	ASTM C650
Frost Resistance	Resistant	ASTM C1026
Water Absorption	<0.50%	ASTM C373
Scratch Hardness	7	Mohs Scale

## Wet Dynamic Coefficient of Friction Range

UPS	0.50 - 0.60	ANSI A326.3
EXT (Textured)	0.60 - 0.70	ANSI A326.3

## Shade & Texture Index

Lisbon Impressions has a shade variation of V2.

V1	V2	V3	V4	V1 Uniform appearance
				V2 Slight Variation
				V3 Moderate Variation
				V4 Substantial Variation

This porcelain tile product is produced with a V2 variation. Expect that the amount of color and texture on each piece may vary slightly. Inspect the product upon delivery and for best results, blend tile from several cartons during installation.

# ROBBINS® Lisbon Impressions™ Porcelain Stone®

AHF Products

3840 Hempland Rd.  
Mountville, PA  
17554

Phone 866 243-2726  
Web Robbins.com

## Recommended Use

Lisbon Impressions UPS is recommended for interior floors, interior walls, countertops, exterior walls, pool waterlines and full linings† in both residential and commercial applications. Lisbon Impressions UPS is not recommended for exterior horizontal surfaces or exterior paving. Lisbon Impressions EXT is recommended for exterior floors and walls in both residential and commercial applications. See Robbins.com for detailed installation instructions.

† Excludes mesh mounted mosaics.

## Care and Maintenance

Regular cleaning is the best way to keep Lisbon Impressions tile looking good for years to come. Use clean, hot water (combined with a household cleaner for more aggressive cleaning). Rinse thoroughly and dry with a soft cloth to prevent water spots. No waxes or sealers are needed. More information regarding the care and maintenance of Robbins products is available at Robbins.com.

## Wet area use for mosaics

Robbins® produces the Lisbon Impressions 2 x 2 and Robbins mosaics with the unpolished (UPS) finish. The ANSI A326.3 wet Dynamic COF of Lisbon Impressions is  $\geq 0.42$ . Their small sizes ensure frequent grout joints which provides traction and drainage. Robbins cannot control situations involving incorrect installation, improper slope to the drain for elimination of standing water and poor surface cleaning.

This information is provided so that customers may make a realistic and informed decision when comparing Lisbon Impressions to other tile products in wet area environments, such as residential/commercial bathrooms, showers, and interior pool decks.

## Crossville® Sample Express

Visit the website to learn more:

**Robbins.com**

### Loose Tile Samples

Sizes may vary depending on product series

Max. of 4 large field tile per order

### Standard Shipping

FedEX Ground

## National Accounts

For over 20 years we have been offering Porcelain tile to commercial customers at National Accounts pricing programs with special discounts. The National Accounts department provides materials forecasting, sales support and samples.

## Trade Organizations



## Environmentally Aware



POURCELAINE



RE-PTG-22  
REV. 12.23