

# ROBBINS®

## Entrée™ Porcelain Stone®

### Available Colors



WB12409 ▶ Travertine Frost



WB12410 ▶ Travertine Café  
Au Lait



WB12411 ▶ Travertine Mist




WB12407 ▶ Concrete Mist



WB12405 ▶ Concrete Frost



WB12406 ▶ Concrete Café  
Au Lait



WB12408 ▶ Classic Marble

### Features and Benefits


- Get immediate access to great design with Entrée™, Robbins' collection of always-on-point and in-stock genuine porcelain tiles
- Featuring some of today's most sought-after looks – including Concrete, Travertine, and white marble visuals
- Entrée™ is perfect for price-conscious projects and those seeking made in the USA products
- All Entrée™ tiles are calibrated in 12x24 and are balanced with 2x2 mosaics and 4x24 bullnose pieces all manufactured in Crossville, TN

# ROBBINS®

# ROBBINS®

## Entrée™ Porcelain Stone®

### Sizes Available in all colors



2 x 2 Square Mosaic  
(Mounted on a  
12 x 12 sheet)

### Sizes & Finishes

#### Field Tile - Calibrated

Available in all colors

Nominal (in)	Actual (in)	Thickness (mm)	Grout Joint (in)	Finish
12 x 24	11-13/16 x 23-13/16	8.5	3/16	UPS

Note: Field tile is calibrated with a 3/16 inch grout joint

#### Mosaics

Available in all colors

Nominal (in)	Sheet Size (in)	Thickness (mm)	Grout Joint (in)	Finish
2 x 2 Mosaic*	11-15/16 x 11-15/16	8.5	3/16	UPS

\* Mounted on a 12 x 12 sheet

#### Coordinating Trim

Available in all colors

Nominal (in)	Actual (in)	Thickness (mm)	Grout Joint (in)	Finish
4 x 24 Single Bullnose	3-13/16 x 23-13/16	8.5	3/16	UPS



4 x 24 Single Bullnose

### Product Performance

Breaking Strength	>400 lbf	ASTM C648
Bond Strength	>200 psi	ASTM C482
Facial Dimension	± 0.15%	ASTM C499
Range of Thickness	0.025"	ASTM C499
Warpage	± 0.20%	ASTM C485
Wedging	± 0.30%	ASTM C502
Chemical Resistance	Unaffected	ASTM C650
Frost Resistance	Resistant	ASTM C1026
Water Absorption	<0.50%	ASTM C373
Scratch Hardness	7	Mohs Scale

### Wet Dynamic Coefficient of Friction Range

UPS	0.42-0.52	ANSI A326.3
-----	-----------	-------------

### Get Planked!

Our Porcelain Stone® products are available in popular plank shapes with no minimum order and quick fulfillment.

See website for more details and sizes.



### Shade & Texture Index

Entrée™ Concrete and Statuario has a shade variation of V2.  
Entrée™ Travertine has a shade variation of V3.

V1	V2	V3	V4	V1 Uniform appearance
				V2 Slight Variation
				V3 Moderate Variation
				V4 Substantial Variation

This porcelain tile product is produced with a V2 variation. Expect that the amount of color and texture on each piece may vary slightly. Inspect the product upon delivery and for best results, blend tile from several cartons during installation.

# ROBBINS®

# ROBBINS®

## Entrée™ Porcelain Stone®

AHF Products

3840 Hempland Rd.  
Mountville, PA  
17554

Phone 866 243-2726  
Web Robbins.com

### Application Areas

Finish	Interior Floors (dry)	Interior Walls (wet/dry)	Exterior Walls	Interior Floors (Standing water/shower floors)	Exterior/Paving	Pool/Fountain Full Lining**	Water Line Pool/Fountains
UPS	✓	✓	✓	✓		✓	✓

\*\* Excludes mesh mounted mosaics. Robbins recommends face mounted or edge mounted mosaics for fully submerged applications. Contact your Robbins sales representative for more information.

NOTE: Trim applications will differ from field tile applications for the same series. For more information on ANSI- A362.3 visit our website at <https://www.robbins.com>

### Recommended Use

Entrée™ is recommended for interior floors, interior walls, countertops, exterior walls, pool waterlines and full linings† in both residential and commercial applications. Entrée™ is not recommended for exterior horizontal surfaces or exterior paving. See Robbins.com for detailed installation instructions.

† Excludes mesh mounted mosaics.

Robbins® produces the Entrée™ 2 x 2 mosaics with the Cross-Sheen (UPS) finish. The ANSI A326.3 wet Dynamic COF of Entrée™ is ≥0.42. Their small sizes ensure frequent grout joints which provides traction and drainage. Robbins cannot control situations involving incorrect installation, improper slope to the drain for elimination of standing water and poor surface cleaning. This information is provided so that customers may make a realistic and informed decision when comparing Entrée™ to other tile products in wet area environments, such as residential/commercial bathrooms, showers, and interior pool decks.

### Care and Maintenance

Regular cleaning is the best way to keep Entrée™ tile looking good for years to come. Use clean, hot water (combined with a household cleaner for more aggressive cleaning). Rinse thoroughly and dry with a soft cloth. No waxes are needed. More information regarding the care and maintenance of Robbins products is available at Robbins.com.

### Our Warranty

AHF Products guarantees that its products will meet or exceed the performance specifications outlined in the most current version of ANSI A137.1 and in the performance data section of the Robbins general product catalog. For complete details and select Resources/Warranties check our website at Robbins.com.

Information listed here is subject to change. Please refer to Robbins.com for the latest, most accurate information.

### Robbins® Sample Express

Visit the website to learn more:  
**Robbins.com**

#### Loose Tile Samples

Sizes may vary depending on product series  
Max. of 4 large field tile per order

#### Standard Shipping

FedEx Ground

#### Trade Organizations



#### Environmentally Aware

